



- Adattatori a cambio rapido e mandrini per maschiatura
- ▲ Quick-change adapters and toolholders for tapping
- Mandrinos e insertos de cambio rápido para roscar

WF 0-1 / WE 0-2

● Adatti per: ▲ Used with: ■ Válido para:	● Mandrino a cambio rapido per maschiatura ▲ Quick-change tapping adapter ■ Mandrino de roscar de cambio rápido	● Tipo ▲ Type ■ Tipo	WF 0	● Cod. ord. ▲ Order No. ■ Código	907 252
---	---	----------------------------	-------------	--	---------

Tipo / Type		WE 0
mm	mm	Cod. ord. ▲ Order No. ■ Código
2,24	1,80	907 259
2,50	2,10	907 253
2,50	2,00	907 260
2,80	2,24	907 261
2,80	2,10	907 254
3,50	2,70	907 255
3,15	2,50	907 262
3,55	2,80	907 263
4,00	3,15	907 264
4,00	3,00	907 256
4,50	3,50	907 265
4,50	3,40	907 257
5,00	4,00	907 266
5,60	4,50	907 267
6,00	4,90	907 258
6,30	5,00	907 268

● Adatti per: ▲ Used with: ■ Válido para:	● Mandrino a cambio rapido per maschiatura ▲ Quick-change tapping adapter ■ Mandrino de roscar de cambio rápido	● Tipo ▲ Type ■ Tipo	WF 1	● Cod. ord. ▲ Order No. ■ Código	906 749
---	---	----------------------------	-------------	--	---------

Tipo / Type		WE 1
mm	mm	Cod. ord. ▲ Order No. ■ Código
2,80	2,10	906 750
3,15	2,50	906 762
3,50	2,70	906 751
4,00	3,15	906 763
4,00	3,00	906 752
4,50	3,40	906 753
4,50	3,55	906 764
6,00	4,90	906 754
6,50	5,00	906 765
7,00	5,50	906 755
7,10	5,60	906 766
8,00	6,20	906 756
9,00	7,00	906 757
9,00	7,10	906 767
10,00	8,00	906 758
11,00	9,00	906 759
11,20	9,00	906 768
12,00	9,00	906 760

● Adatti per: ▲ Used with: ■ Válido para:	● Mandrino a cambio rapido per maschiatura ▲ Quick-change tapping adapter ■ Mandrino de roscar de cambio rápido	● Tipo ▲ Type ■ Tipo	ISO 30 POT 2	● Cod. ord. ▲ Order No. ■ Código	58 771 01
---	---	----------------------------	-------------------------	--	-----------

Tipo / Type		WE 2
mm	mm	Cod. ord. ▲ Order No. ■ Código
6,0	4,9	907 128
6,3	5,0	907 138
7,0	5,5	907 129
7,1	5,6	907 139
8,0	6,3	907 140
8,0	6,2	907 130
9,0	7,0	907 131
9,0	7,1	907 141
10,0	8,0	907 132
10,0	8,0	907 142
11,0	9,0	907 133
11,2	9,0	907 143
12,0	9,0	907 134
12,5	10,0	907 144
14,0	11,0	907 135
14,0	11,2	907 145
16,0	12,0	907 136
18,0	14,5	907 137

- Tecniche di serraggio alternative per maschi, idonee per unità di maschiatura SUHNER
- ▲ Alternative toolholder systems for taps suitable for use with SUHNER tapping units
- Otros sistemas de portaherramientas válidos para las unidades de roscado SUHNER

● Adatti per: ▲ Used with: ■ Válido para:	● Dimensioni di montaggio ▲ Assembly dimensions ■ Dimensiones para montaje	● Descrizione ▲ Description ■ Descripción	● Tipo ▲ Type ■ Tipo	● Cod. ord. ▲ Order No. ■ Código
GEM 6		● Mandrino B 12, campo di serraggio: Ø 0,5-8,0 mm Forza di serraggio: max. 30 Nm. ▲ Drill chuck B 12, clamping range 0.5-8.0 mm diameter. Clamping force maximum 30 Nm. ■ Portabrocas B 12, gama diámetros: Ø 0,5-8,0 mm. Fuerza de cierre: 30 Nm máx.	WT 1	59 538 01
GEM 16		● Mandrino B 16, campo di serraggio: Ø 1,0-13,0 mm Forza di serraggio: max. 80 Nm. ▲ Drill chuck B 16, clamping range 1.0-13.0 mm diameter. Clamping force maximum 80 Nm. ■ Portabrocas B 16, gama diámetros: Ø 1,0-13,0 mm. Fuerza de cierre: 80 Nm máx.	WT 2	59 538 02
GEM 20 C GEM 20 B GEM 20 A BEX 15		● Mandrino SK 30, campo di serraggio: Ø 1,0-13,0 mm Forza di serraggio: max. 80 Nm. ▲ Drill chuck SK 30, clamping range 1.0-13.0 mm diameter. Clamping force maximum 80 Nm. ■ Portabrocas SK 30, gama diám.: Ø 1,0-13,0 mm. Fuerza de cierre: 80 Nm máx.	ISO 30 / WT 4	59 540 02

● Adattatori per accoglienza nel trapano per maschiatori GSX, pagine D 50 e D 51	▲ Adapter for mounting in drilling machine for tapping attachment GSX, pages D 50 and D 51	■ Adaptador para montaje en taladro de roscadores GSX, págs. D 50, D 51, en taladro
--	--	---

Cono
Cone
Cono

Pinza
Tapping
Pinza

Morse
Morse
Morse

SK-DIN 2080

MAS-BT

Cilindro
Cylinder
Cilindro

● Adattamento ▲ Adaption ■ Adaptación	Morse				DIN 2080				MAS-BT		Zyl.					
	MK 1	MK 2	MK 3	MK 4	SK 30 M 12	SK 40 M 16	SK 45 M 20	SK 50 M 24	BT 40 M 16	BT 50 M 24	Ø 8	Ø 10	Ø 12	Ø 14	Ø 16	Ø 20
3 Jt	903 910	903 911	903 912	903 913	906 620	904 741	906 624	904 742	906 628	906 630	-	-	-	-	-	-
33 Jt	903 906	903 907	903 908	903 909	904 740	903 930	906 623	906 626	906 627	906 629	8252 201	8252 202	8252 203	8252 206	8252 204	8252 207
4 Jt	-	903 915	903 916	903 917	-	906 622	906 625	905 100	-	-	-	-	-	-	-	-
B-16	903 940	903 941	903 942	903 943	906 632	906 634	-	906 635	906 637	906 638	-	-	-	-	-	-
1/8"-24	906 605	906 606	906 607	-	-	-	-	-	-	-	-	-	-	-	-	-
1/2"-20	906 608	906 609	906 610	-	-	-	-	-	-	-	-	-	-	-	-	-
3/8"-16	-	906 611	906 612	-	-	-	-	-	906 640	906 641	-	-	-	-	-	-
1/4"-20	906 613	903 919	903 921	903 923	903 929	903 931	-	903 932	906 642	906 643	-	-	903 936	-	903 937	903 938

